

ALUMINIUM TRIPOD WITH WINCH



DW-200



DW-1040

- Light aluminium construction with built-in rope winch
- Simple transport due to telescopic height adjustment
- Spikes as standard

Accessories:

- Rubber plates (for solid ground)
- Safety chain (for smooth ground)

All models are equipped with rope winch, crank, rope and swivelling load hook.

For rapid winding/unwinding of the unloaded load the winches are equipped with a direct drum drive and a load drive (except model DW-200). The crank can be removed even in a loaded condition (except model DW-200).

Special designs made of steel tube on request.

Order No.	Model	Carrying Capacity kg	Length Of Support L Min./Max. m	Clearance Height ¹⁾ H Min./Max. m	Total Lifting Height m	Spreading Angle ¹⁾ B Min./Max. m	Rope Lines	Weight Approx. kg
144 200	DW-200	200	1,18 / 1,88	0,94 / 1,58	5,00	0,95 / 1,50	1	20
144 500	DW-500	500	2,10 / 2,50	1,70 / 2,10	5,00	1,50 / 2,00	1	35
144 503	DW-530	500	2,40 / 3,00	2,00 / 2,50	7,00	1,90 / 2,50	1	45
144 577	DW-1000	1.000	2,40 / 3,00	1,90 / 2,40	7,00	1,90 / 2,50	2	45
144 504	DW-1040 ²⁾	1.000	2,85 / 4,00	2,40 / 3,40	7,00	2,20 / 3,00	2	69

¹⁾ Max. spreading angle (25°)

²⁾ For static reasons the upper part of the support with winch is made of galvanised steel.